

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 amended by
Regulation (EU) 2020/878

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : DASA DS-408 22 liter clear
Productcode: : DS-408

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Adhesive
stance/Mixture

Recommended restrictions : For industrial and professional use only.
on use

1.3 Details of the supplier of the safety data sheet

Company : DASA International B.V.

Address : Bergerweg 62-M
1815AE Alkmaar
The Netherlands
+31 (0) 725719917
E-mail address : info@dasa-international.com

1.4 Emergency telephone number

Emergency telephone number : DASA: +31(0)72-5719917 (ma-vr 09:00-17:00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquid, Category 1	H224: Extremely flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aquatic Acute, Category 1	H400: Very toxic to aquatic life.
Aquatic Chronic, Category 1	H410: Very toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H224 Extremely flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves/eye protection.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.

Hazardous components which must be listed on the label:

cyclohexane
Naphta (petroleum), hydrotreated light
acetone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Naphta (petroleum), hydrotreated light	64742-49-0 265-151-9	Flam. Liq. 2; H225 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 (Respiratory system)	>= 10 - < 20
Zinc bis(dibutyldithiocarbamate)	136-23-2 205-232-8 01-2119535161-51-0000	Aquatic Acute 1; H400 (M=1) Aquatic Chronic 1; H410 (M=10) Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335	< 0,5
cylohexane	110-82-7 203-806-2 01-2119463273-41-0000	Flam. Liq. 2; H225 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 (Respiratory system)	>= 20 - < 40
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49-0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 10 - < 20
Substances with a workplace exposure limit :			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37-0000	Flam. Gas 1; H220 Press. Gas Compr. Gas; H280	>= 20 - < 50
----------------	--	---	--------------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : If on clothes, remove clothes.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may even occur after several hours;
therefore medical observation for at least 48 hours after the
accident.
- If inhaled : Remove person to fresh air. If signs/symptoms continue, get
medical attention.
If breathing has stopped, apply artificial respiration.
In case of unconsciousness bring patient into stable side posi-
tion for transport.
- In case of skin contact : Wash off immediately with soap and plenty of water while
removing all contaminated clothes and shoes.
Call a physician if irritation develops or persists.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical atten-
tion if eye irritation develops or persists.
- If swallowed : Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water mist Dry powder Carbon dioxide (CO ₂) Alcohol-resistant foam
Unsuitable extinguishing media	:	Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting	:	May release toxic, irritating and/or corrosive gases. In case of fire, the following substance(s) may occur: Carbon monoxide
---------------------------------------	---	--

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
Further information	:	In the event of fire, wear self-contained breathing apparatus. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Remove all sources of ignition. Use personal protective equipment. Use breathing protection against the effects of fumes/dust/aerosol. Evacuate personnel to safe areas. Ensure adequate ventilation.
----------------------	---	---

6.2 Environmental precautions

Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities.
---------------------------	---	---

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Non-sparking tools should be used. Ensure adequate ventilation. Send for recovery or disposal in suitable containers.
-------------------------	---	---

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid formation of dust and aerosols.

Take note of emission threshold.

Use solvent-proof equipment.

Ensure that suitable extractors are available on processing machines.

Handle with care.

Keep eye wash bottle available on working place.

Avoid release to the environment.

Keep out of reach of children.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on an open flame or other ignition source.

Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition - No smoking. Keep away from children.

Use only with adequate ventilation.

Advice on protection against fire and explosion : Keep product and empty container away from heat and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. May form explosive mixtures in air. Highly volatile, flammable constituents are released during processing. In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Keep tightly closed in a dry, cool and well-ventilated place. Protect against light.

Further information on storage conditions : Keep containers tightly closed in a dry, cool and well-ventilated place. Store in a cool place. Heat will increase pressure and may lead to the container exploding.

Advice on common storage : Do not store together with oxidizing and self-igniting products.

7.3 Specific end use(s)

Specific use(s) : No further relevant information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC
Further information: Indicative				
		OELV - 8 hrs (TWA)	1.000 ppm 1.920 mg/m3	IE OEL
cyclohexane	110-82-7	TWA	200 ppm 700 mg/m3	2000/39/EC
Further information: Indicative				
		OELV - 8 hrs (TWA)	200 ppm 700 mg/m3	IE OEL
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC
Further information: Indicative				
		OELV - 8 hrs (TWA)	500 ppm 1.210 mg/m3	IE OEL

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
dimethyl ether	Workers	Inhalation	Systemic, long-term	1894 mg/m3
	Workers	Eye contact	Local effects	
acetone	Workers	Inhalation	Local, short-term	2420 mg/m3
	Workers	Inhalation	Systemic, long-term	1210 mg/m3
	Workers	Eye contact	Local effects	
	Workers	Dermal	Systemic, long-term	186 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
dimethyl ether	Soil	0,045 mg/kg
	Marine sediment	0,069 mg/kg
	Marine water	0,016 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water	0,155 mg/l
	Fresh water sediment	0,681 mg/kg
acetone	Soil	29,5 mg/kg
	Sewage treatment plant	100 mg/l
	Fresh water	10,6 mg/l
	Fresh water sediment	30,4 mg/kg
	Marine water	1,06 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

	Marine sediment	3,04 mg/kg
--	-----------------	------------

8.2 Exposure controls

Engineering measures

Please take care on national and local requirements.

Personal protective equipment

Eye protection : Tightly fitting safety goggles or equipment with better protection

Hand protection
Material : Nitrile rubber or equipment with better protection

Remarks : Direct contact with the product must be avoided by organizational measures.

The glove material has to be impermeable and resistant to the product/the substance/the preparation.
The exact break through time can be obtained from the protective glove producer and this has to be observed.
The gloves need to be disposed after the penetration time and replaced by new ones.
Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

For the permanent contact gloves made of the following materials are suitable:

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from Ansell or other suppliers (penetration time: 480 min).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber (minimum thickness: 0.7 mm; penetration time: 15 min)

As protection from splashes gloves made of the following materials are suitable:

Nitril (minimum thickness 0.12 mm), Disposable gloves with long cuffs

After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

Skin and body protection : Protective clothing

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

Respiratory protection	: Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In case of brief exposure or low pollution (exceeding of TLV) use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air. Ensure that suitable extractors are available on processing machines.
Filter type	: Combined particulates and organic vapour type or equipment with better protection (A-P)
Protective measures	: Keep away from food, drink and animal feedingstuffs. Instantly remove any soiled and impregnated garments. Wash hands before breaks and immediately after handling the product. Avoid contact with the eyes and skin. Store protective clothing separately.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: gaseous
Colour	: natural colour
Odour	: characteristic
Odour Threshold	: is not determined
Melting point/freezing point	: is not determined
Boiling point/boiling range	: 55,8-56,6 °C
Upper explosion limit / Upper flammability limit	: 18,6 %(V)
Lower explosion limit / Lower flammability limit	: 1,3 %(V)
Flash point	: < -42 °C
Auto-ignition temperature	: is not determined
Decomposition temperature	: Not applicable
pH	: is not determined

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

Viscosity
Viscosity, kinematic : is not determined

Solubility(ies)
Water solubility : not miscible or difficult to mix

Partition coefficient: n-
octanol/water : no data available

Density : 0,79 g/cm³

Relative vapour density : is not determined

9.2 Other information

Explosives : Product is not explosive. However, formation of explosive vapour/air mixtures is possible.

Evaporation rate : is not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

No decomposition if used according to the specifications.

10.3 Possibility of hazardous reactions

Hazardous reactions : Develops readily flammable vapours/fumes.

10.4 Conditions to avoid

Conditions to avoid : Heat may lead to dangerous pressure build-up in sealed container.

10.5 Incompatible materials

Materials to avoid : No further relevant information available.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

SECTION 12: Ecological information

12.1 Toxicity

Components:

cyclohexane:

Toxicity to fish : LC50 (Fathered minnow, Pimephales promelas): 4,53 mg/l Exposure time: 96 Hours
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,9 mg/l
Exposure time: 48 Hours
Test Type: static test

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

dimethyl ether:

Partition coefficient: n-octanol/water : log Pow: 0,10

12.4 Mobility in soil

Product:

Mobility : Medium: Soil
Remarks: Do not allow product to reach ground water, water bodies or sewage system.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Do not dispose of waste into sewer.
Hand over to disposers of hazardous waste.
The generation of waste should be avoided or minimized wherever possible.
Incinerate under controlled conditions in accordance with all local and national laws and regulations.
Disposal must be made according to official regulations.

These EU waste code numbers are recommendations for waste accruing through the use of adhesives and sealants. Any waste produced from organic solvents or other dangerous substances (according GHS) listed under section 3 of this safety datasheet is itself classified as dangerous (*).

Waste accruing during application:

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Waste accruing during cleaning:

08 04 11* adhesive and sealant sludges containing organic solvents or other dangerous substances
08 04 12 adhesive and sealant sludges other than those mentioned in 08 04 11

Waste packaging:

15 01 01 paper and cardboard packaging
15 01 02 plastic packaging
15 01 04 metallic packaging
15 01 10* packaging containing residues of or contaminated by dangerous substances.

Contaminated packaging : Disposal must be made according to official regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 3501
RID	:	UN 3501
IMDG	:	UN 3501
IATA (Cargo)	:	UN 3501
IATA (Passenger)	:	UN 3501 Not permitted for transport

14.2 UN proper shipping name

ADR	:	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (DIMETHYL ETHER, CYCLOHEXANE)
RID	:	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (DIMETHYL ETHER, CYCLOHEXANE)
IMDG	:	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (DIMETHYL ETHER, CYCLOHEXANE)
IATA (Cargo)	:	Chemical under pressure, flammable, n.o.s. (DIMETHYL ETHER, CYCLOHEXANE)
IATA (Passenger)	:	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. Not permitted for transport

14.3 Transport hazard class(es)

ADR	:	2
RID	:	2
IMDG	:	2.1
IATA (Cargo)	:	2.1
IATA (Passenger)	:	Not permitted for transport

14.4 Packing group

ADR		
Packing group	:	Not assigned by regulation
Classification Code	:	8F
Hazard Identification Number	:	23
Labels	:	2.1
Tunnel restriction code	:	(B/D)
RID		
Packing group	:	Not assigned by regulation
Classification Code	:	8F

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

Hazard Identification Number : 23

Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1

EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 218

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger) : Not permitted for transport

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (SVHC, Article 59) : Compliant

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Compliant

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Compliant

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

Council Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors : Neither banned nor restricted

Directive 2000/53/EC of the European Parliament and of the Council of 18 September 2000 on end-of life vehicles : Compliant

Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment, Annex II : Compliant

Council Regulation (EC) No 273/2004 on drug precursors : Compliant

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : acetone

REACH - List of substances subject to authorisation (Annex XIV) : Compliant

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. : acetone (ANNEX II)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E1 Hazardous to the Aquatic Environment

P5a FLAMMABLE LIQUIDS

18 Liquefied flammable gases (including LPG) and natural gas

Minimum Qualifying Quantity of Lower Tier Requirement :10 t
Maximum Qualifying Quantity of Higher Tier Requirement :50 t

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
		Volatile organic compounds (VOC) content: 796 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements

H224	:	Extremely flammable liquid and vapour.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.
H410	:	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Flam. Liq.	:	Flammable liquids
Press. Gas	:	Gases under pressure
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
IE OEL	:	Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2
2000/39/EC / TWA	:	Limit Value - eight hours
2006/15/EC / TWA	:	Limit Value - eight hours
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

rate associated with x% response; EmS - Emergen- cy Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration as- sociated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La- boratory Practice; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - Interna- tional Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test popula- tion; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - Interna- tional Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Ef- fect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic sub- stance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quanti- tative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Re- striction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : This safety datasheet only contains information relating to safety and does not replace any product information or prod- uct specification.

Modified data compared to the previous version

The following sections have been updated:

- Section 1
- Section 2
- Section 7
- Section 9
- Section 15
- Section 16

Contact Point : Prepared by: Global Regulatory Department
info@dasa-international.com

Classification of the mixture:

Flam. Liq. 1	H224
Skin Irrit. 2	H315
STOT SE 3	H336

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-408 22 liter clear

Version	Revision Date:	SDS Number:	Date of last issue: 03.06.2025
2.0	09.07.2025	100000031152	Date of first issue: 07.03.2025
	Print Date:		
	16.07.2025		

Aquatic Chronic 2

H410

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

EN / EN