

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : DASA DS-504 500ml. clear

Productcode : DS-504

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Adhesive
stance/Mixture

Recommended restrictions : For industrial use only.
on use

1.3 Details of the supplier of the safety data sheet

Company : DASA International B.V.

Address : Bergerweg 62-M
1815AE Alkmaar
The Netherlands
+31 (0) 725719917

E-mail address of person : info@dasa-international.com
responsible for the SDS

1.4 Emergency telephone

Emergency telephone : DASA: +31(0)72-5719917 (mon-fri 09:00-17:00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous ingredients which must be listed on the label:

Hydrocarbons, C6, isoalkanes, <5% n-hexane
pentane
acetone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regu-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

lation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0 931-254-9 649-328-00-1 01-2119484651-34-0000	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
pentane	109-66-0 203-692-4 601-006-00-1 01-2119459286-30-0000	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 10 - < 20
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49-0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 10
Substances with a workplace exposure limit :			
dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37-XXXX	Flam. Gas 1; H220 Press. Gas Compr. Gas; H280	>= 30 - < 50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

4.1 Description of first-aid measures

- | | | |
|-------------------------|---|---|
| General advice | : | If on clothes, remove clothes.
Show this safety data sheet to the doctor in attendance.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. |
| If inhaled | : | Remove person to fresh air. If signs/symptoms continue, get medical attention.
If breathing has stopped, apply artificial respiration.
In case of unconsciousness bring patient into stable side position for transport. |
| In case of skin contact | : | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Call a physician if irritation develops or persists. |
| In case of eye contact | : | Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists. |
| If swallowed | : | Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|-------|---|---|
| Risks | : | Causes skin irritation.
May cause drowsiness or dizziness. |
|-------|---|---|

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|--|
| Treatment | : | No further relevant information available. |
|-----------|---|--|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|--------------------------------|---|--|
| Suitable extinguishing media | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water mist
Dry powder
Carbon dioxide (CO ₂)
Alcohol-resistant foam |
| Unsuitable extinguishing media | : | Do NOT use water jet. |

5.2 Special hazards arising from the substance or mixture

- | | | |
|---------------------------------------|---|--|
| Specific hazards during fire fighting | : | May release toxic, irritating and/or corrosive gases.
In case of fire, the following substance(s) may occur:
Carbon monoxide |
|---------------------------------------|---|--|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

5.3 Advice for firefighters

Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
Further information	:	In the event of fire, wear self-contained breathing apparatus. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Remove all sources of ignition. Use personal protective equipment. Use breathing protection against the effects of fumes/dust/aerosol. Evacuate personnel to safe areas. Ensure adequate ventilation.
----------------------	---	---

6.2 Environmental precautions

Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities.
---------------------------	---	---

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Non-sparking tools should be used. Ensure adequate ventilation. Send for recovery or disposal in suitable containers.
-------------------------	---	---

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Local/Total ventilation	:	Use only with adequate ventilation.
Advice on safe handling	:	Avoid formation of dust and aerosols. Take note of emission threshold. Use solvent-proof equipment. Ensure that suitable extractors are available on processing

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

machines.
Handle with care.
Keep eye wash bottle available on working place.
Avoid release to the environment.
Keep out of reach of children.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Do not spray on an open flame or other ignition source.
Do not spray on a naked flame or any incandescent material.
Keep away from sources of ignition - No smoking. Keep away from children.

Use only with adequate ventilation.

Advice on protection against fire and explosion : Keep product and empty container away from heat and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. May form explosive mixtures in air. Highly volatile, flammable constituents are released during processing. In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Keep tightly closed in a dry, cool and well-ventilated place. Protect against light.

Further information on storage conditions : Keep containers tightly closed in a dry, cool and well-ventilated place. Store in a cool place. Heat will increase pressure and may lead to the container exploding.

Advice on common storage : Do not store together with oxidizing and self-igniting products.

7.3 Specific end use(s)

Specific use(s) : No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
------------	---------	-------------------------------	--------------------	-------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version 1.0 Revision Date: 25.11.2025 SDS Number: 100000035068 Date of last issue: -
Print Date: 26.11.2025 Date of first issue: 06.11.2025

dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC
Further information: Indicative				
		OELV - 8 hrs (TWA)	1.000 ppm 1.920 mg/m3	IE OEL
pentane	109-66-0	TWA	1.000 ppm 3.000 mg/m3	2006/15/EC
Further information: Indicative				
		OELV - 8 hrs (TWA)	1.000 ppm 3.000 mg/m3	IE OEL
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC
Further information: Indicative				
		OELV - 8 hrs (TWA)	500 ppm 1.210 mg/m3	IE OEL

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
dimethyl ether	Workers	Inhalation	Systemic, long-term	1894 mg/m3
	Workers	Eye contact	Local effects	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Workers	Eye contact	Local effects	
	Workers	Dermal	Systemic, long-term	300 mg/kg
	Workers	Inhalation	Systemic, short-term	1286,4 mg/m3
	Workers	Inhalation	Local, long-term	837,5 mg/m3
	Workers	Inhalation	Local, short-term	1066,67 mg/m3
	Workers	Inhalation	Systemic, long-term	1,9 mg/m3
Resin acids and Rosin acids, esters with glycerol	Workers	Inhalation	Local, long-term	10 mg/m3
	Workers	Dermal	Systemic, long-term	5 mg/kg
	Workers	Eye contact	Local effects	
acetone	Workers	Inhalation	Local, short-term	2420 mg/m3
	Workers	Inhalation	Systemic, long-term	1210 mg/m3
	Workers	Eye contact	Local effects	
	Workers	Dermal	Systemic, long-term	186 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
dimethyl ether	Soil	0,045 mg/kg
	Marine sediment	0,069 mg/kg
	Marine water	0,016 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water	0,155 mg/l
	Fresh water sediment	0,681 mg/kg
Resin acids and Rosin acids, esters with glycerol	Soil	462,06 mg/kg
	Fresh water sediment	2317,75 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

	Marine sediment	231,78 mg/kg
	Marine water	0,01 mg/l
	Sewage treatment plant	2,525 mg/l
	Fresh water	0,1 mg/l
acetone	Soil	29,5 mg/kg
	Sewage treatment plant	100 mg/l
	Fresh water	10,6 mg/l
	Fresh water sediment	30,4 mg/kg
	Marine water	1,06 mg/l
	Marine sediment	3,04 mg/kg

8.2 Exposure controls

Engineering measures

Please take care on national and local requirements.

Personal protective equipment

Eye protection : Tightly fitting safety goggles or equipment with better protection

Hand protection
Material : Nitrile rubber or equipment with better protection

Remarks : Direct contact with the product must be avoided by organizational measures.

The glove material has to be impermeable and resistant to the product/the substance/the preparation.
The exact break through time can be obtained from the protective glove producer and this has to be observed.
The gloves need to be disposed after the penetration time and replaced by new ones.
Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

For the permanent contact gloves made of the following materials are suitable:

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Alphatec®/Barrier 02-100 PE-underglove from Ansell or other suppliers (penetration time: 480 min).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber (minimum thickness: 0.7 mm; penetration time: 15 min)

As protection from splashes gloves made of the following materials are suitable:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

Nitril (minimum thickness 0.12 mm), Disposable gloves with long cuffs

After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

Skin and body protection : Protective clothing

Respiratory protection : Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
In case of brief exposure or low pollution (exceeding of TLV) use breathing filter apparatus.
In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.
Ensure that suitable extractors are available on processing machines.

Filter type : Combined particulates and organic vapour type or equipment with better protection (A-P)

Protective measures : Keep away from food, drink and animal feedingstuffs.
Instantly remove any soiled and impregnated garments.
Wash hands before breaks and immediately after handling the product.
Avoid contact with the eyes and skin.
Store protective clothing separately.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: aerosol
Color	: natural colour
Odor	: characteristic
Odor Threshold	: is not determined
Melting point/freezing point	: is not determined
Boiling point/boiling range	: -25 °C
Flash point	: < -41 °C
Autoignition temperature	: is not determined

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

Decomposition temperature	:	Not applicable
pH	:	is not determined
Viscosity		
Viscosity, kinematic	:	> 20,5 mm ² /s (40 °C)
Solubility(ies)		
Water solubility	:	not miscible or difficult to mix
Partition coefficient: n-octanol/water	:	no data available
Density	:	0,75 g/cm ³
Relative vapor density	:	is not determined

9.2 Other information

Explosives	:	Product is not explosive. However, formation of explosive vapour/air mixtures is possible.
Evaporation rate	:	is not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

No decomposition if used according to the specifications.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Develops readily flammable vapours/fumes.
---------------------	---	---

10.4 Conditions to avoid

Conditions to avoid	:	Heat may lead to dangerous pressure build-up in sealed container.
---------------------	---	---

10.5 Incompatible materials

Materials to avoid	:	No further relevant information available.
--------------------	---	--

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

pentane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 9,87 mg/l
Exposure time: 96 Hours
Method: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 9,74 mg/l
Exposure time: 48 Hours
Test Type: static test

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Partition coefficient: n-octanol/water : log Pow: 2,2 - 6,1 (23 °C)
pH: 6,2
GLP: yes

acetone:

Partition coefficient: n-octanol/water : log Pow: -0,24

dimethyl ether:

Partition coefficient: n-octanol/water : log Pow: 0,10

12.4 Mobility in soil

Product:

Mobility : Medium: Soil
Remarks: Do not allow product to reach ground water, water bodies or sewage system.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---	---

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	Do not dispose of with domestic refuse. Do not dispose of waste into sewer. Hand over to disposers of hazardous waste. The generation of waste should be avoided or minimized wherever possible. Incinerate under controlled conditions in accordance with all local and national laws and regulations. Disposal must be made according to official regulations.
---------	---	---

These EU waste code numbers are recommendations for waste accruing through the use of adhesives and sealants. Any waste produced from organic solvents or other dangerous substances (according GHS) listed under section 3 of this safety datasheet is itself classified as dangerous (*).

Waste accruing during application:

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Waste accruing during cleaning:

08 04 11* adhesive and sealant sludges containing organic solvents or other dangerous substances
08 04 12 adhesive and sealant sludges other than those mentioned in 08 04 11

Waste packaging:

15 01 01 paper and cardboard packaging
15 01 02 plastic packaging
15 01 04 metallic packaging
15 01 10* packaging containing residues of or contaminated by dangerous substances.

Contaminated packaging	:	Disposal must be made according to official regulations.
------------------------	---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

SECTION 14: Transport information

14.1 UN number or ID number

ADR	: UN 1950
RID	: UN 1950
IMDG	: UN 1950
IATA	: UN 1950

14.2 UN proper shipping name

ADR	: AEROSOLS
RID	: AEROSOLS
IMDG	: AEROSOLS (Hydrocarbons, C6, isoalkanes, <5% n-hexane)
IATA	: Aerosols, flammable

14.3 Transport hazard class(es)

ADR	: 2
RID	: 2
IMDG	: 2.1
IATA	: 2.1

14.4 Packing group

ADR	
Packing group	: Not assigned by regulation
Classification Code	: 5F
Labels	: 2.1
Tunnel restriction code	: (D)

RID	
Packing group	: Not assigned by regulation
Classification Code	: 5F
Hazard Identification Number	: 23
Labels	: 2.1

IMDG	
Packing group	: Not assigned by regulation
Labels	: 2.1
EmS Code	: F-D, S-U

IATA (Cargo)	
Packing instruction (cargo aircraft)	: 203
Packing instruction (LQ)	: Y203
Packing group	: Not assigned by regulation
Labels	: Flammable Gas

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

IATA (Passenger)

Packing instruction (passenger aircraft)	: 203
Packing instruction (LQ)	: Y203
Packing group	: Not assigned by regulation
Labels	: Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (SVHC, Article 59)	: Compliant
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	: Compliant
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Compliant
Council Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors	: Neither banned nor restricted
Directive 2000/53/EC of the European Parliament and of the Council of 18 September 2000 on end-of life vehicles	: Compliant

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment, Annex II : Compliant

Council Regulation (EC) No 273/2004 on drug precursors : Compliant

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Compliant

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. acetone (ANNEX II)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

E2 ENVIRONMENTAL HAZARDS

Minimum Qualifying Quantity of Lower Tier Requirement :200 t

Maximum Qualifying Quantity of Higher Tier Requirement :500 t

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 64,99 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

AIIC : On the inventory, or in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

ENCS	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
REACH	:	On the inventory, or in compliance with the inventory

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements

H220	:	Extremely flammable gas.
H225	:	Highly flammable liquid and vapour.
H280	:	Contains gas under pressure; may explode if heated.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Flam. Liq.	:	Flammable liquids
Press. Gas	:	Gases under pressure
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
IE OEL	:	Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2
2000/39/EC / TWA	:	Limit Value - eight hours
2006/15/EC / TWA	:	Limit Value - eight hours
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Test-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

ing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Contact Point : Prepared by: Global Regulatory Department
info@dasa-international.com

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

DASA DS-504 500ml. clear

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.11.2025	100000035068	Date of first issue: 06.11.2025
	Print Date:		
	26.11.2025		

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IE / EN